



◎E-GLASS CHOPPED STRAND MAT◎


EMULSION MAT

[APPLICATION]

- ◎ E-glass chopped strands binded by emulsion adhesive. Applying for hand lay-up.
- ◎ Applying for reinforced UP resin.

[PRODUCT PROPERTIES]

- ◎ Even thickness .even stiffness.
- ◎ Easy wet out and impregnating.
- ◎ Filament have outstanding anti-washability and easy wet out and impregnating.
- ◎ Excellent processability in moulded parts, applying for diversity moulding and processing. Specially in opened moulding and closed moulding.
- ◎ Excellent mechanical strength during production of finished product.



TECHNICAL SPECIFICATION:


Product code	Roll width (mm)	Individual weight (g/m ²)	Compatible resin	Applying process	LOD:	Moisture content%
EMCL	250-3000	225-900	UP	Hand lay-up	2.0-8.0	≤0.20

Specific product properties indicated in quality analysis report.

PACKAGING:

CTG E-glass emulsion mat ,each roll covering by polyethylene plastic bag ,then placed into cardboard box .and set on pallet .each pallet vertical stack 12 cardboard boxes. Or horizontal stack 9 /6 cardboard boxes. Each cardboard box is weight 35-50kg. The pallet shall no be higher than 2 layers and the cardboard box shall no be higher than 3 layers.

Please remark followings in purchasing order: ◎product code ◎individual weight and roll width. ◎quantity ◎packaging ◎special needs can meet according to customer requirements.



STORAGE:

Product shall be placed under dryness condition and shall no be open the covering membrane until applying.